

L 41151-66 EWT(d)/EWT(m)/ENP(k)/ENP(w)/ENP(v) IJP(c) EM/WW

ACC NR: AP6021547

(A)

SOURCE CODE: UR/0198/66/002/006/0063/0070

39
388

AUTHOR: Shubin, I. A. (Novosibirsk); Shkutin, L. I. (Novosibirsk)

ORG: Institute of Hydrodynamics, Siberian Department, AN SSSR (Institut gidrodinamiki, Sibirskoye otdeleniye AN SSSR)

TITLE: Experimental investigation of the stability of plane conical shells under static pressure loading

26

SOURCE: Prikladnaya mekhanika, v. 2, no. 6, 1966, 63-70

TOPIC TAGS: shell deformation, conic shell structure, shell structure stability, static load test

ABSTRACT: A method is proposed and results given of testing plane conical shells having an angle of elevation of $\pi/36$, $\pi/18$, $\pi/12$ radians, walls 0.1—0.6 mm thick, and base diameter of 138 mm for stability under an external pressure. The shells were manufactured by the galvanic method out of copper. Two types of loading (pneumatic and hydraulic) and restriction of the shells at the base (fixed and movable) were used. The process of deforming the shells

Card 1/2

L 41151-66

ACC NR: AP6021547

from the start of loading to complete reversing in a state of equilibrium close to specular reflection of the initial state is described in detail. The magnitudes of the breaking loads and the forms of undulation of the shells are established. It was found that the loss of stability of carefully manufactured plane conical shells occurs in two stages. The first stage is the transition of the axisymmetric equilibrium form to an asymmetric form with an optimal number of waves fully determined for the shell of the given geometry (the formation of a number of waves other than optimal indicates the presence of initial imperfections in the shell). The occurring asymmetric equilibrium form proves to be unstable at first (unstable in the small) but then becomes stable. The replacement of the stability of the asymmetric form by instability signifies the second stage of loss of shell stability. Equilibrium proves to be unstable over a long path of deformation (instability in the large). Under "dead weight" loads, overturning of the shell occurs which ends with its complete reversal. The authors express deep gratitude to E. I. Grigolyuk on whose suggestion this investigation was performed. Orig. art. has: 5 tables and 6 figures.

SUB CODE: 13/ SUBM DATE: 11Oct65/ ORIG REF: 002

Card 2/2 hs

SHUMIN, I. D.

"Hybridization of Local Rye and Wheat," Selek. i Semenov., Vol.15, No.4, pp 59-60,
1948

Translation U-3400, 30 Apr 53

SHUMIN, I. B.

Sowing

Role of scientific farming in increasing resistance of fall seedlings to freezing and thinning out. Sov. agron., 10, no. 9, 1952.

9. MONTHLY LIST OF RUSSIAN ACQUISITIONS, Library of Congress, November 1952. Uncl.

SHUBIN, I. D.

"Turkmenistan Wheat." Cand Agr Sci, Tashkent Agricultural Inst,
Min Higher Education USSR, Tashkent, 1955. (KL, No 10, Mar 55)

SO: Sum No. 670, 29 Sep 55 - Survey of Scientific and Technical Dis-
serattions Defended at USSR Higher Educational Institutions (15)

SHUBIN, I.G.

Mass destruction of rodents by torrential rains in the Kazakh Uplands.

Trudy Inst.zool.AN Kazakh.SSR 4:236-237 '55.

(MIRA 10:1)

(Chetskiy District--Rodentia)

(Rain and rainfall)

SHUBIN, I. G.

Acad Sci Kazakh SSR. Inst of Zoology

SHUBIN, I. G.- "The ecology and economic significance of Mongolian 'pishchaki' and Streltsov voles under the conditions of the Kazakh uplands." Acad Sci Kazakh SSR. Inst of Zoology. Alma-Ata, 1956.
(Dissertation for the Degree of Candidate in Biological Sciences.)

SO: Knizhnaya Letopis' No. 13, 1956.

14-57-7-15089
Translation from: Referativnyy zhurnal, Geografiya, 1957, Nr 7,
p 146 (USSR)

AUTHOR: Shubin, I. G.

TITLE: Effects of Geographical Environments on the Multi-
plication of the Mongolian Creeper (Vliyaniye
geograficheskoy sredy na razmnozheniye mongol'skoy
pishchukhi)

PERIODICAL: Tr. In-ta zool. AN KazSSR, 1956, Vol 6, pp 61-77

ABSTRACT: Mongolian creepers reproduce from April to June in
the Kazakh highlands and have three litters a year.
Gestation takes approximately 25 days, and an average
litter is eight. Three days after they are born the
young are covered with fur; after nine or ten days
they open their eyes; after 16 or 18 days they leave
their burrows, and after 23 or 25 days they begin to
shift for themselves. Most of them begin to multiply

Card 1/2

Effects of Geographical Environments (Cont.)

14-57-7-15089

when they are eight to ten months old, though some do so at one to one and a half months. Their rutting season begins 15 to 20 days earlier on the slopes with southern exposure than on northern slopes. The creeper of the Kazakh highlands is larger than the Mongolian and its young are bigger. Observations showed that the young of the first litter were largest, while in Mongolia those of the third litter were largest. Breeding takes place a month later in Mongolia. This difference is occasioned by seasonal variations in the vegetation.

Card 2/2

L. D.

SHUBIN, I.G.

Infestation of the Mongolian pika with larvae of the botfly
Oestromyia falax Grunin, 1949. Trudy Inst. zool. AN Kazakh. SSR
9:242 '58. (MIRA 11:7)
(Klik region--Botflies) (Basaga region--Botflies) (Parasites--Pikas)

SHUBIN, I.G.

Ecology of Strel'tsov's vole (*Alticola strelzovi* Kastsch) in the
highland of Kazakhstan. Trudy Inst.zool.AN Kazakh SSR 10:87-113
'59. (MIRA 12:7)

(Kazakhstan--Field mice)

SHUBIN, I.G.

Ecology of the Mongolian pika (*Ochotona pallasi* Gray) in the high-
land of Kazakhstan. Trudy Inst.zool.AN Kazakh SSR 10:114-132
'59. (MIRA 12:7)

(Karaganda Province--Pikas)

STRAUTMAN, Ye.I.; SHUBIN, I.G.

Biology of the voles *Lagurus lagurus* and *Microtus gregalis* in
northern Kazakhstan. Trudy Inst. zool. AN Kazakh. SSR 13:45-53
'60.

(Kazakhstan--Field mice)

(MIRA 13:7)

SHUBIN, I.G.

Partial destruction of populations of the vole *Lagurus lagurus*
by heavy rains. Trudy Inst. zool. AN Kazakh. SSR 13:93-99 '60.
(MIRA 13:7)
(Shoindykol' region--Field mice)

SHUBIN, I. G., CAND BIO SCI, "ECOLOGY AND ECONOMIC
SIGNIFICANCE OF THE TREE CREEPER AND ~~THE STREET~~
the *high*
FIELD MOUSE UNDER CONDITIONS OF KAZAKH ~~UP~~ LANDS." TOMSK,
PUBLISHING HOUSE OF TOMSK UNIV, 1961. (TOMSK STATE UNIV
IM V. V. KUYBYSHEV). (KL, 3-61, 212).

SHUBIN, I.G.

Ecology of the subterranean vole *Ellobius talpinus* Pall. in central
Kazakhstan. Zool. zhur. 40 no.10:1543-1551 0 '61. (MIRA 14'9)

1. Institute of Zoology, Academy of Sciences of the Kazakh S.S.R.,
Alma-Ata.

(Kazakhstan--Field mice)

SHUBIN, I.G.

Food of predatory animals and birds of the Kazakh Hills, Trudy Inst.
zool. AN Kazakh. SSR 17:183-191 '62.

New data on the distribution of some rodents in Tselinograd Province.
Ibid.:242-244 (MIRA 17:2)

SHUBIN, I.G.

Time of reproduction in the bobac. Zool. zhur. 41 no.5:750-754
My '62. (MIRA 15:6)

1. Institute of Zoology, Academy of Sciences of the Kazakh
S.S.R., Alma-Ata.

(TSelinograd Province—Marmots)

SHUBIN, I.G.

Time of hibernation of the steppe marmot and the lesser suslik in
central Kazakhstan. Zool. zhur. 42 no.2:274-281 '63. (MIRA 16:3)
(Kazakhstan—Marmots) (Kazakhstan—Susliks) (Hibernation)

SHUBIN, I.G.

Interrelationship between bobac and predatory animals in central
Kazakhstan. Trudy Inst. zool. AN Kazakh. SSR. 23:191-196 '64.
(MIRA 17:11)

KRYL'TSOV, A.I.; SHUBIN, I.G.

Ecology of *Cricetulus eversmanni* Br. and *Phodopus sungorus* Pall. Zool.
zhur. 43 no.7:1062-1070 '64. (MIRA 17:12)

1. Kazakh Institute of Plant Protection, and Institute of Zoology.
Academy of Sciences of the Kazakh S.S.R., Alma-Ata.

SEBEN, I.C.

Reproduction of the Lesser pika *Ochotona pusilla* Pall. 7col. 24ur.
M. no. 80937-341 1966. (MRE 18:10)

1. Institut zoologii N Burdakovy SFS, Irkutsk.

KREPKOGORSKAYA, T.A.; NASIBULINA, F.I.; SHUBIN, I.N.

Results of the examination of murine rodents as leptospira carriers
in Alma-Ata Province. Izv. AN Kazakh. SSR. Ser.med. i fiziol. no.1:
55-59 '59. (MIRA 13:1)

(ALMA-ATA PROVINCE--LEPTOSPIRA)

SHUBIN, I.N., inzh.

Estimating the stability of rocks in tunneling. Transp.stroi.
10 no.5:45-47 My '60. (MIRA 13:7)
(Tunneling) (Rocks--Cleavage)

SHUBIN, I.N., inzh.

Determining the degree of fracturing of rocks in tunnel workings.

Transp. stroi. 10 no. 12:45-46 D '60.

(MIRA 13:12)

(Rocks)

(Tunneling)

SHUBIN, K.

Training for skilled pilots. Grazhd.av. 18 no.1:14-15 Ja '61.

(MIRA 14:3)

1. Nachal'nik Shkoly vyssheyetnoy podgotovki Grazhdanskogo ~~vozdushnogo~~ flota.

(Ul'yanovsk—Flight training)

SHUBIN, K.

IUzhino-Sibirskaia magistral'. [South-Siberian trunk line]. (In Zemlia sovetskaia 1950, p. 408).

DLC: KD18.Z4

SO: SOVIET TRANSPORTATION AND COMMUNICATIONS, A BIBLIOGRAPHY, Library of Congress Reference Department, Washington, 1952, Unclassified.

SHUBIN, K.A., inzhener.

Standard precast concrete elements for one-story industrial
buildings. Bet.i zhel.-bet. no.3:80-88 Mr '56. (MIRA 9:7)
(Precast concrete)

SHUBIN, K.A., red.; PEVZNER, A.S., red.izdatel'stva; NAGISHKINA, T.M., tekhn.
red.; STEPANOVA, E.S., tekhn.red.

[Principal regulations governing standard designs for industrial
buildings] Osnovnye polozheniia po unifikatsii konstruktsii
proizvodstvennykh zdani. Izd.2-oe. Moskva, Gos.izd-vo lit-ry po
stroitel'no arkhit., 1957. 13 p. (MIRA 10:12)

1. Russia (1923- U.S.S.R.) Gosudarstvennyy komitet po delam
stroitel'stva.

(Factories)

SHUBIN, K.A., inzhener.

Methods for a further expansion in using precast reinforced
concrete elements in the mass production of buildings. Biul.
stroi. tekhn. 14 no.2:1-4 P '57. (MLRA 10:4)

1. Gosstroy SSSR.
(Precast concrete construction)

SHUBIN, K.A., inzhener.

Results of the competition for standard precast reinforced concrete elements for multistoried industrial buildings. Biul. stroi. tekhn. 14 no.5:1-7 My '57. (MIRA 10:6)

1. Gosudarstvennoye stroitel'stvo SSSR.
(Architecture--Designs and plans--Competitions)
(Industrial buildings) (Precast concrete construction)

SHUBIN, K.A., inzh.

Unifying planning and design decisions concerning industrial
buildings. *Biul. stroi. tekhn.* 14 no.10:16-21 O '57. (MIRA 10:12)

1. Gosstroy SSSR.

(Factories--Design and construction)

SHUBIN, K.A., inzh.

Introducing progressive structural solutions in construction.
Bul. stroi. tekhn. 15 no.4:1-8 Ap '58. (MIRA 11:5)

1. Gosstroy SSSR.
(Girders) (Steel, Structural)

OSTROVSKIY, M.Ye., arkhitektor; SHUBIN, K.A., inzh.

Shortcomings in planning standard industrial structures. Prom.
stroil. 38 no.3:20-22 '60. (MIRA 13:6)
(Factories--Design and construction)

SHUBIN, K.A.

Standardization of three-dimensional plans for buildings and structures. Biul. stroi. tekhn. 18 no.10:9-12 0 '61.

(MIRA 17:3)

1. Zamestitel' nachal'nika otdela tipovogo proyektirovaniya Gosstroya SSSR.

SHUBIN, K.A., inzh., red.; MURATOV, I.V., inzh., red.; PETROVA, V.V.,
red.izd-va; TEMKINA, Ye.L., tekhn. red.

[Basic regulations SN 223-62 concerning the standardization
of three-dimensional plans and design details of industrial
buildings] Osnovnye polozheniia po unifikatsii ob"emno-
planirovochnykh i konstruktivnykh reshenii promyshlennykh
zdanii (SN 223-62). Moskva, 1962. 16 p. (MIRA 16:2)

1. Russia (1923- U.S.S.R.) Gosudarstvennyy komitet po delam
stroitel'stva.

(Industrial buildings--Design and construction)

9.3130
1.2310

22939
S/125/61/000/006/003/010
D040/D112

AUTHORS: Gorbanskiy, V. V., Shubin, L. V., Khudyshev, A. F. (Moscow)

TITLE: Equipment for precision electron-beam welding of refractory metals and alloys

PERIODICAL: Avtomaticheskaya svarka, no. 6, 1961, 21-30

TEXT: The authors describe a new experimental installation developed for welding refractory metals and alloys by an electron beam in a vacuum. The article contains detailed design information. The unit is shown in a photograph (Fig. 2) and diagram (Fig. 1). It consists of an electron-optic system, i.e. an electronic gun with focusing and deflecting systems; a high-voltage rectifier; one feed unit for the focusing and deflecting system and one for the modulator, a work chamber, a mechanism rotating and moving the workpiece, an evacuating system with a high-vacuum and a forevacuum pump. The electron-optic system (Fig. 3) is attached by a flange to the work chamber. Its parts are connected by vacuum-tight joints with aluminum or copper shims. The cathode leg of the electron gun is fixed in a ceramic bulb and its output terminals connected to a heater, a lanthanum boride

Card 1/ 9

Equipment for precision electron-beam welding... ²²⁹³⁹ S/125/61/000/006/003/010
D040/D112

cathode, and a focusing and a modulating electrode. The anode unit is a cylindrical water-cooled pipe. The cathode leg is connected to the anode unit by the flange. There are one central and six side holes in the cylinder top. Accelerated electrons move through the central hole and air is evacuated through the side holes. The electron gun is powered from the rectifier and the modulator; the feed source for the focusing and deflecting system is inside the unit; the controls are on the front panel. When the electron gun works with pulses (to obtain higher beam density and to reduce heating), the feed voltage is modulated. Pulses and intervals are adjustable in ten steps between 0.01 and 1.2 sec. The 20 cubic decimeter capacity work chamber is cylindrical, welded from stainless 1x18H9T (1Kh18N9T) steel. Replaceable workpiece holding devices are provided for welding circular and straight seams. A vacuum of $8 \cdot 10^{-5}$ mm Hg is maintained in the chamber. The gun system is shown in a diagram (Fig. 4). Boride cathodes are used because of their stability at high current densities (above 10 amp/cm²) and because they require no activation time. Heating to 1600°C is sufficient for steady operation of the cathode. The work life of most of the boride cathodes is 250-300 hours. The replaceable lanthanum boride cathodes have active surface diameters of 3.0, 4.2 and 5.4 mm. A tungsten wire

Card 2/9

22939

S/125/61/000/006/003/010

Equipment for precision electron-beam welding... DO4C/D112

spiral is used for heating the cathodes. Three different electron guns are designed for cathodes of different diameters. Power can be varied over a wide range. Practically all refractory metals with a thickness of 0.005 to 5 mm can be welded. The distance from the anode outlet to work surface is 340 mm, because of the size of the work chamber. The focusing system is a magnetic lens, i.e. a rectangular coil, a portion of which is placed in an iron screen. The electron beam passes for a considerable part of its passage in the equipotential space of the anode pipe. The external electric and magnetic fields have no effect on it, therefore calculation of the focussing system may be simplified by assuming that only the forces repelling the space charge are acting, and that the magnetic lens is "short". The spread of the electron beam may be calculated by the Mayns - Watson (Russian spelling) equation

$$\frac{l_1}{r_0} = \left(\frac{l}{2m} \right)^{\frac{1}{2}} \frac{v}{\sqrt{2}} 2 \int_0^{\sqrt{1n \frac{R}{r_0}}} l x^2 dx = 1.021 \frac{v^{\frac{3}{2}} (Kv)}{\sqrt{2} (e r_0)} F \frac{R}{r_0}, (1)$$

Card 3/9

Equipment for precision electron-beam welding...

22939
S/125/61/000/006/003/010
D040/D112

where e and m are the charge and the mass of electron; I - the beam current; v - the anode tube potential (in respect to the cathode). The equation (1) describes directly the initial parallel beam shape. In the magnetic lens the beam converges (Fig. 7). The article includes a calculation example. It is very approximate, and the basic dimensions for the focussing system were determined finally in experiments. The best position for the magnetic lens was found to be $l_1 = 120$ mm and $l_2 = 220$ mm (Fig. 7), and the proper current for focussing a 150 m-amp beam at 15,000 volt to be 1000 - 1050 v-amp. The deflecting system is the same as used for TV tubes and consists of four coils connected by pairs in series and at an 180° angle. The coils are wound on special arbors and consist of 5 sections, with maximum winding density at the coil end to produce a uniform magnetic field. The formula for calculating the ampere-turns of coils (Ref. 13: M. Ya. Mulyarov, Elektronno-luchevyye pribory [Electron-beam instruments], Gosenergoizdat, 1954 is

$$I_N = \frac{2.65 d_{int} \sin \theta \sqrt{U_a [V]}}{l_0},$$

Card 4/9

22939

Equipment for precision electron-beam welding... S/125/61/000/006/003/010
D040/D112

where d_{int} - is the internal diameter of deflecting system; l_0 - the effective coil length ($l_0 = l + 10\%l$); l - the coil length; δ - the maximum deflection angle. The undistorted deflection angle determined in experiments was $3-5^\circ$, which means that the beam may be deflected 10-15 mm off center without changing the focus. Further work is in progress on determination of beam pressure on a metal pool, during welding and heat distribution in the metal outside the weld. Conclusions. 1) The system with replaceable cathodes permits welding-current regulation between 100 w and 10 kw. 2) The high-voltage rectifier and modulator permit pulse welding. 3) The experimental unit makes possible the welding of circular and straight seams by an electron beam in a vacuum. 4) Vacuum-tight joints can be obtained on refractory metals. There are 10 figures and 15 references: 5 Soviet-bloc and 8 non-Soviet bloc. The four latest references to English-language publications read as follows: G. Burton and Wm. L. Frankhouser, Electron-beam Welding, "Welding Journal", No. 10, 38, 1959, S.401-409; Production Welding with Electrons, "Electronic Industries", April, pp 76-94, 1959; Electron-beam Welding, "American Machinist", February, 23, pp 94-96, 1959; Electron-beam Welding, "Engineering", April 1959.

SUBMITTED: December 7, 1960
Card 5/9

17
BLEYVAS, I.M.; LUKOSHKOV, V.S.; MESTECHKIN, Ya.I.; KHOMICH, V.B.; SHEREL', L.A.;
SHUBIN, L.V.

Solution of problems in electron optics and superhigh frequency
electronics using mathematical modeling techniques. Radiotekh. i
elektron. 8 no.10:1764-1775 0 '63, (MIRA 16:10)

L 3/2/66-00 JMT(1) JEF(c) AT/AD

ACC NR: AT6022256

SOURCE CODE: UR/0000/66/000/000/0063/0067

AUTHOR: Yegorov, G. P.; Mestechkin, Ya. I.; Shubin, L. V.

53

ORG: none

841

TITLE: Investigation of speed-distribution of electrons in magnetically-formed beams

SOURCE: Vsesoyuznaya nauchnaya sessiya, posvyashchennaya Dnyu radio. 22d, 1966.
Sektsiya elektroniki. Doklady. Moscow, 1966, 63-67

TOPIC TAGS: electron beam, SHF, magnetron

ABSTRACT: The results are briefly reported of an experimental investigation of electron-speed spectra (axial components) in an axisymmetrical cylindrical electron beam formed by a longitudinal magnetic field. The electron gun and the magnetic field were so designed that the electron beam had minimum pulsation and was near-laminar. The distribution of current density over the beam diameter, at 5 mm from the electron-optical system, is shown. Findings: (1) The measured spectrum width exceeds that of the Maxwellian distribution; (2) The spectrum width decreases from the edge to the center of the beam; (3) Maximum electron energies differ from the anode potential, which can be explained by the presence of a tangential velocity component and by a rotation of electrons. Orig. art. has: 4 figures. [03]

SUB CODE:09 / SUBM DATE: 09Apr66 / ORIG REF: 005 / OTH REF: 002

Card 1/1

L 26674-66 EWT(d)/EWP(h)/EWP(l)

ACC NR: AP6009551

SOURCE CODE: UR/0413/66/000/005/0093/0094

AUTHORS: Amel'kovich, I. I.; Artamonov, Yu. G.; Dyatlov, Ye. S.; Magirovskiy, N. P.; Novozhilov, Yu. I.; Orlov, S. F.; Pikkuvirta, P. O.; Podkovyrin, A. I.; Polyachenko, V. A.; Senchenko, L. P.; Fedosyev, O. V.; Shubin, L. V. 3 2

ORG: none B

TITLE: Machine for gathering, hauling, and transportation of felled trees. Class 45, No. 179539 [announced by Onega Tractor Factory (Onezhskiy traktorny zavod); Leningrad Kirov Factory (Leningradskiy Kirovskiy zavod); Leningrad Forestry Technical Academy im. S. M. Kirov (Leningradskaya lesotekhnicheskaya akademiya)] 14

SOURCE: Izobreteniya, promyshlennyye obraztsy, tovarnyye znaki, no. 5, 1966, 93-94

TOPIC TAGS: tractor, forestry, forestry product

ABSTRACT: This Author Certificate presents a machine for hauling, gathering, and transporting felled trees, consisting of a mono-axle tractor, semitrailer with steering axle connected with the tractor by a universal joint, and a hoist. To insure a continuous pick-up of felled trees and their loading on the machine, the latter is equipped with a movable boom, to the end of which is attached a pincer clamp. To improve the maneuverability of the machine, the movable boom is mounted on the tractor frame and the pick-up device on the frame of the semi-trailer. To

Card 1/2

UDC: 629.114.4:634.0.377.4 2

L 26674-66

ACC NR: AP6009551

0

prevent damage to the movable parts, the latter are protected by means of pipe fastened above the saddle hitch device. To facilitate the loading of large packets of trees, a pulley is attached to the protective pipe (see Fig. 1).




Fig. 1. 1 - pick-up assembly; 2 - hoist;
3 - saddle-hitch device; 4 - movable boom;
5 and 6 - power cylinders; 7 - pincer clamp;
8 - mono-axle tractor; 9 - semitrailer;
10 - steering axle of semitrailer; 11 - protective pipe; 12 - pulley.

Orig. art. has: 1 diagram.

SUB CODE: 13,02/ SUBM DATE: 15Jun64

Card 2/2 BLG

SHUBIN, L. (Sverdlovskaya obl.)

Noise generator. Radio no.11:49 N '62.
(Oscillators, Electric)
(Radio filters)

(MIRA 15:12)

OSIPOV, Lev Georgiyevich, kand.tekhn.nauk; SERBINOVICH, Pavel Petrovich;
KRASENSKIY, Viktor Yevgen'yevich. Prinimal uchastiye SHUBIN, L.F.,
inzh. BOLDYREV, A.K., kand.tekhn.nauk, retsenzent; MARTYNOV,
A.P., red.; GRIGORCHUK, L.A., tekhn.red.

[Public and industrial buildings; architectural and structural
designs and building elements] Grazhdanskie i promyshlennye
zdanija; arkhitekturno-konstruktivnye skhemy i elementy zdaniy.
Izd.2., perer. Pod obshchei red. L.G.Osipova. Moskva, Gos.
izd-vo "Vysshaya shkola," 1961. 470 p. (MIRA 15:2)
(Public buildings) (Industrial buildings)

OSIFOV, Iev Georgiyevich, kand. tekhn. nauk; SERBINOVICH, Pavel Petrovich; KRASENSKIY, Viktor Yevgen'yevich; Prinizial uchastiye SHUBIN, L.F.; KUPERSHCHIK, L.S., red.

[Public and industrial buildings; architectural and construction designs and building elements] Grazhdanskie i promyshlennye zdaniia; arkhitekturno-konstruktivnye skhemy i elementy zdaniia. Izd.3., perer. Moskva, Vysshaya shkola, 1964. 483 p. (MIRA 17:8)

ALIMPIYEV, G.G.; VOLOKHOV, V.F.; SHUBIN, L.N.

Unit for the drying and reclamation of transformer oil. Rats.
predl. na gor. elektrotransp. no.9:61-63 '64.

(MIRA 18:2)

1. Upravleniye tramvaya Iipetska.

VOLKHOV, V.F.; SHUBIN, L.N.

Shoes for cables with a cross section up to 800 mm². Pats. predl.
na gor. elektrotransp. no.9:63-64 '64.

(MIRA 18:2)

1. Upravleniye tramvaya Lipetska.

SHUBIN, M.

23405

Raschety pri proizvodstve toplenogo tvorozhnogo syra. Moloch.
Prom-st', 1949, No. 7, c. 39-40.

SO: LETOPIS NO. 31, 1949.

SHUBIN M.

USSR (600)

Cheese

Compting mixtures for making cheese-curd products Mol. prom 13 No 4, 1952

9. Monthly List of Russian Accessions, Library of Congress, June 19~~7~~³/₂, Uncl.

SHUBIN, M.

The beacon is shining brightly. Metallurg 8 no.10:22-23 0 '63.
(MIRA 16:12)

1. Redaktsiya gazety "Cherepovetskiy metallurg."

FEDOROV, D.I.; SHUBIN, M.A.; NEDOREZOV, I.A.; MASHKOVICH, O.N.;
LUR'YE, G.K.

Basis for the prospective typification of earthmoving machines
in the construction of transportation systems. Transp. stroi.
15 no.9:43-45 S '65. (MIRA 18:11)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut transportnogo
stroitel'stva.

CHERNAVSKIY, V.P., kand.tekhn.nauk.; SHUBIN, M.A., inzh.

Constructing railroad lines on bakhans. Transp.stroi. 8
no.4:15-17 Ap '58. (MIRA 12:12)

(Railroad--Construction)

PETROV, L.K., kand. tekhn. nauk; TISKOVICH, S.M., inzh.; SHUBIN, M.I., inzh.

Porous-slotted ceramic bricks and products made from them.
Stroi. mat. 9 no.7:9-11 J1 '63. (MIRA 16:11)

SHUBIN, M.M., kand. sel'skokhozyaystvennykh nauk.

Importance of sweet clover in the agriculture of steppe regions
of the Altai Territory. Zemledelie 6 no.11:62-66 II '58.
(Altai Territory--Sweet clover) (HRA 11:11)

ROBIN, 2.4.

Natural forage lands of the steppe and forest-steppe of the
Altai Territory and their improvement. Trudy TSSBS no.6:355-362
163. (MIRA 17:7)

SHUBIN, M. A., fel'dsher (selo Lizinovka Voronezhskoy oblasti)

Work of a medical and obstetrical station. Fel'd. i akush. 27
no.5:45-48 My '62. (MIRA 15:7)

(LIZINOVKA---MEDICAL CARE)

SHUBIN, M.A., inzh.

Efficiency of continuous-action earth-working machinery. Transp.
stroil. 12 no.8:36-39 Ag '62. (MIRA 15:9)
(Earthmoving machinery)

SHUBIN, M.M., kand. sel'skokhoz. nauk

Tasks of meadow management in the Altai. Zemledelie 27 no.1:
65-70 Ja '65. (MIRA 18:3)

ASS, Boris Abramovich; ZHUKOVA, Nina Mikhaylovna; BRASLAVSKIY, D.A.,
kand.tekhn.nauk, retsenzent; SHUBIN, M.P., inzh., retsenzent;
MILOSLAVOV, B.A., kand.tekhn.nauk, red.; TUBYANSKAYA, F.G.,
izdat.red.; ORESHKINA, V.I., tekhn.red.

[Parts and units of aeronautical instruments and their design]
Detali i uzly aviatsionnykh priborov i ikh raschet. Moskva, Gos.
nauchno-tekhn.izd-vo Oborongiz, 1960. 357 p.

(MIRA 14:3)

(Aeronautical instruments)

SHUBIN, M. Ye.

20932 Shubin, M. Ye. Tipovaya Kafedra molochnogo dela. Sbornik dokladov Pervoy Vsesoyuz. Konf-tsii po moloch. delu. M., 1949, s. 44-52

SC: LETOPIS ZHURNAL STATEY - Vol. 28, Moskva, 1949

SHUBIN, M.Ye.

Speeding up the basic technological operations in the manufacture
of kefir. Izv.vys.ucheb.zav.; pishch.tekh. no.5:74-80 '59.
(MIRA 13:4)

1. Vologodskiy molochnyy institut, kafedra tekhnologii moloka i
molochnykh produktov.
(Kefir)

SHUBIN, Mikhail Yefimovich, dots.; BRUSANOV, N.A., red.; GUREVICH, M.M.,
tekhn. red.

[Production of high quality milk in dairy farms] Proizvodstvo vy-
sokokachestvennogo moloka na fermakh. Moskva, Gos.izd-vo sel'khoz.
lit-ry, 1960. 52 p. (MIRA 14:12)

1. Vologodskiy molochnyy institut (for Shubin).
(Milk)

SHUBIN, N. A.

USSR/Engineering - Die Casting,
Equipment

Mar 52

"Die Performance in the Process of Die Casting,"
N. A. Shubin, Engr, Moscow Automobile Plant imeni
I. V. Stalin

"Litey Proizvod" No 3, pp 14, 15

Outlines work of die and demonstrates use of method
for static calcn of pressures in designing dies
with various relative positions of die cavity,
plunger and gate.

21272

SOV/137-58-8-17335

Translation from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 8, p 163 (USSR)

AUTHOR: Shubin, N.A.

TITLE: Practice of Application of a Special Paste for the Local Protection of Machine Parts from Carburization (Opyt primeneniya spetsial'noy pasty dlya mestnoy zashchity detaley ot tsementatsii)

PERIODICAL: V sb.: Mashinostroitel' Belorussii, Nr 4, Minsk, 1957, pp 140-141

ABSTRACT: For the local protection of machine parts from carburization (C) it is recommended that a paste consisting (in grams) of minium 40, aluminum oxide 80, calcined talc 160, water glass (sp gr 1.40) 700, be used instead of expensive brazing. The first three components are screened through a 140-mesh sieve, mixed in with the water glass and then applied onto the degreased surface of the machine part in a thin layer which protects against carburization in the gas C at 950-1000°C. The consumption of paste for a two-layer coating is ~ 1 kg per m² of surface. It is recommended that narrow openings and threaded surfaces be coated with a thinner layer. While packing

Card 1/2

SOV/137-58-8-17335

Practice of Application of a Special Paste (cont.)

the machine parts in baskets for the C, they should be placed in such a way that the areas covered with the paste would not touch the surface of articles intended to be carburized. this will prevent an unintentional application of the paste which melts at 950-1000°.

A.B.

1. Metals--Carbonization
2. Metals--Coatings

Card 2/2

SOV/137-58-8-17487

Translation from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 8, p 183 (USSR)

AUTHOR: Shubin, N.A.

TITLE: Passivation of Zinc Coatings (Passivirovaniye tsinkovykh pokrytiy)

PERIODICAL: V sb.: Mashinostroitel' Belorussii. Nr 4. Minsk, 1957, p 144

ABSTRACT: The introduction into industry of a solution for the (5-25-second) passivation (P) of Zn coatings, containing 50-150 g/l CrO_3 , and 5-50 g/l NaCl at 15-25°C is reported. The P is accomplished immediately after the removal of the article from the zincing bath and the washing with cold water. After this they are dried in a drying cabinet at 70-80°. The indications of good P are: a) The passive film after drying does not rub off by hand. b) a 10-20 times increase in the resistance of the Zn coating in the moist chamber at 60-70° compared to the non-passivated coatings.

V.G.

Zinc coating--Passivity

Card 1/1

SHUBIN, N.A.; LUTOVINOV, Ye.M.

Semiautomatic die for investment casting. Lit.proizv. no.2:44-45
F '60. (MIRA 13:5)
(Precision casting)

SHUBIN, N.A.

Problem of the mode of action of additions of tin, lead, and
and mercury on cathodic polarization in zincate electrolytes.
Vestsi AN BSSR. Ser. Fiz.-tekh. nav. no. 4:53-62 '60.

(MIRA 14:1)

(Zincate)

(Polarization (Electricity))

SHUBIN, N. A.[Subinas, N.]; MATULIS, Yu.Yu.[Matulis, J.]

Effect of casein on the cathodic polarization of zinc in zincate electrolytes. Liet ak darbai no.3:169-176 '61.

1. Predstavleno Institutom khimii i khimicheskoy tekhnologii Akademii nauk Litovskoy SSR.

TIMOKHIN, N.A.; SHUBIN, N.A.

Semiautomatic production line in the manufacture of hide glue.
Kozh.-obuv.prom. 3 no.7:13-15 J1 '61. (MIRA 14:9)
(Glue) (Assembly-line methods)

SHUBIN, N.G.

Two new hosts of the warble fly *Oestromyia leporina* Pall.
(Diptera, Hypodermatidae) [with summary in English]. Ent. oboz.
39 no.1:213 '60. (MIRA 13:6)

1. Tomskiy gosudarstvennyy universitet.
(Anzhero-Sudzhensk region--Warble flies) (Parasites--Field mice)

SHUBIN, N.G.

Feeding habits of the chipmunk Tamias sibiricus in the Tom' Basin.
Zool. zhur. 41 no.12:1902-1905 D '62. (MIRA 16:3)

1. Department of Vertebrate Zoology, State University of Tomsk.
(Tom' Valley--Chipmunks)

SHUBIN, N.G.

Reproduction of the chipmunk in the Tom' basin. Zool. zhur. 4² no.6:
910-917 '64. (MIRA 17:12)

1. Department of Vertebrate Zoology, Tomsk State University.

SHUBIN, N.G.

Mammalian fauna of the Kuznetsk Alatau and Salair Ridge.
Izv. Alt. otd. Geog. ob-va SSSR no.5:148 '65.

(MIRA 18:12)

1. Tomskiy gosudarstvennyy universitet.

GRUNIN, K.Ya.; SHUBIN, N.G.

New warble fly *Teba schubini* Grunin gen. et sp. n. (Diptera,
Hypodermatidae) from Siberia. Zool. zhur. 44 no.9:1414-1415
'65. (MIRA 18:10)

1. Zoologicheskiy institut AN SSSR, Leningrad i Tomskiy
gosudarstvennyy universitet.

KOVAL'CHUK, N.R.; SHUBIN, N.I.

Increasing the efficiency of the development of cis-Carpathian
oil fields. Neft. i gaz. prom. 3:15-18 JI-6 '65.
(MIRA 18:11)

SOV/93-58-8-13/15

AUTHOR: Shubin, N. I. and Andruschko, V. I.

TITLE: ~~Hydraulic Fracturing of Beds in Deep Free Flowing~~
Wells at Oilfield No. 1 of the Dolinaneft' NPU (Gidrav-
licheskiy razryv plastov v glubokikh fontannykh skva-
zhinakh neftepromysla No.1 NPU Dolinaneft')

PERIODICAL: Neftyanoye khozyaystvo, 1958, Nr 8, pp. 65-69 (USSR)

ABSTRACT: The article states that the hydraulic fracturing of
free flowing wells at Oilfield No. 1 of the Dolinaneft'
NPU began in 1954. The wells of this oilfield were
2,200-2,400 m. deep and the reservoir pressure amounted
to 270 atm. Regular commercial petroleum from the
oilfield or oily crude from the Sagaydak oilfield
served as fracturing fluids, but the fracturing results
were poor due to the low viscosity of the fluids.
During the search for a more suitable fluid an analysis
was made of petroleum products derived from oily crude
at the L'vovskiy neftepererabatyvayushchiy zavod
(L'vov Refinery) and of petroleum products derived from

Card 1/3

Hydraulic Fracturing of Beds (Cont.)

SOV/93-58-8-13/15

high paraffin and tar content crude at the Drogobychskiy neftepererabatyvayushchiy zavod No. 2 (Drogobych Refinery No. 2). Analyzed furnace mazout from the L'vov refinery had good viscosity characteristics, but it could not be tested under industrial conditions due to supply difficulties. An analysis of three mixtures of goudron consisting of unoxidized tars and "plus filtrate" (the latter consisting of spindle oil cleansed of paraffin by the filtration method) also disclosed good viscosity characteristics. These three mixtures of goudron and spindle oil were made of first run high tar and paraffin content crude rprocessed at the Drogobych Refinery No. 2. The analysis results of the three blends are given in Table 1. It was disclosed that blend No. 2 has the most desirable characteristics as a fracturing fluid and consequently it was subjected to industrial tests. The fracturing fluid and the sand were pressed down the test well by means of eight TsA-400 pumps and the results are shown in Fig. 1. At the beginning Vol'sk sand was employed,

Card 2/3

Hydraulic Fracturing of Beds (Cont.)

SOV/93-58-8-13/15

but due to delivery difficulties it was replaced with Ternopol' sand whose fractional composition is given in Table 2. The fracturing results obtained by means of the new fracturing fluid are shown by Fig. 2. The success of this fluid at the Dolinaneft' oilfield was acknowledged by the Borislav and Bitkov oilfields of the Petroleum, Gas, and Chemical Administration of the Stanislav Economic Region where it found wide application. The authors recommend goudron-spindle oil blends of the type produced by the Drogobych Refinery No. 2 for fracturing formations containing crude of high tar and paraffin content, and furnace mazout of the type produced by the L'vov Refinery for the fracturing of formations containing oily crudes. There are 2 tables and 2 figures.

1. Petroleum--Production
2. Petroleum--Viscosity
3. Wells--Processing
4. Hydraulic systems--Performance

Card 3/3

SHUBIN, N.I.

Geology, conditions governing the formation, and the oil
potential of the Orovka prospecting region. Neft. i gaz.
prom. no.2:9-13 Ap-Je '64. (MIRA 17:9)

SHUBIN, N.I.

Formation of Carpathian-type oil fields; based on the changes in the properties of petroleum as revealed by the petroleum of the Dolina field. Nefte. i gaz.prom. no.1:13-16 Ja-Mr. '65.

(MIRA 18:8)

SAUBIN, N. V.

"Problems of Angular Measurements in First- and Second-Class Networks." Sub 26
Jan 51, Moscow Inst of Engineers of Geodesy, Aerial Photography and Cartography

Dissertations presented for science and engineering degrees in Moscow during 1951.

SO: Sum. No. 480, 9 May 55

SHUBIN, N. V.

"Certain Results of the Study of Tick-Borne Encephalitis," by N. V. Shubin, Trudy Tomskogo Nauchno-Issledovatel'skogo Instituta Vaktsin i Syvorotok (Works of the Tomsk Scientific Research Institute of Vaccines and Sera), Vol 6, 1955, pp 51-66, (from Sovetskoye Meditsinskoye Referativnoye Obozreniye, No 15, 1956, pp 29-30, abstract by K. Gorbunova)

"Analysis of the literature from the archives of the Clinic of Nervous Diseases, Tomsk Medical Institute, showed that diseases of the tick-borne encephalitis type have been recorded since 1897. The data studied led the author to distinguish and to classify six forms of tick-borne encephalitis: (1) poliomyelitic, (2) polioencephalomyelitic, (3) polioencephalitic, (4) encephalitic, (5) polioradiculoneuritic, and (6) Kojevnikoff's epilepsy. In all the forms of tick-borne encephalitis, the author notes all the course variations -- subacute, "neprogrediyyentnoye," and "progrediyyentnoye" [probably poorly defined and well-defined stages] -- which occur with varying frequency in the different forms of encephalitis. The disease course with poorly delineated stages has a two-wave character. In the pathogenesis of a chronic (progrediyyentnoye) course, the reactivity of the macroorganism and its capacity to overcome the virus play a significant part. It is necessary to administer convalescent serum and hyperimmune horse serum in the acute stage; and to perform physiotherapy, massage, and therapeutic gymnastics in the paralytic stage. Kojevnikoff's epilepsy is treated surgically, by excision of the motor centers of the convulsed extremities." (U)

Sum. 1391

SHUBIN, N.V., burovoy master

Enforce work discipline for preventing accidents. Bezop.truda v prom.
2 no.4:30 Ap '58. (MIRA 11:4)

1. Sokolovogorskaya kontorn bureniya.
(Oil fields--Safety measures)

SHUBIN, N V

6-58-4-18/18

AUTHOR: None Given

TITLE: Chronicle (Khronika)

PERIODICAL: Geodeziya i Kartografiya, 1958, Nr 4, pp. 79-80 (USSR)

ABSTRACT: From February 15, to February 22, 1958 the XII. Scientific and Technical Conference took place at the Novosibirsk Institute of Engineers of Geodesy, Aerial Photography, and Cartography. The results obtained by the work performed by the Institute in 1957 were made known. The conference was attended by about 200 geodesists and cartographers of 20 scientific- and production-organizations of Novosibirsk, Stalingrad, Kuybyshev, Sverdlovsk, Omsk, Tomsk, Abakan, Krasnoyarsk. Among them were the geodesists occupied with building the hydraulic power plants of Kuybyshev, Novosibirsk and Krasnoyarsk. Lectures delivered at the plenary session: S.A.Kapustin on "Critique of Modern ~~Reformist~~ Theories of State Monopoly Capitalism", R.G.Bannova on "The Penetration of Marxist Ideas into Russia between the Forties and Seventies of the 19th Century", N.V.Shubin on "Soviet Geodesy and Cartography on the Occasion of the 40th Anniversary of the Great Socialist October Revolution", M.N.Kolobkov on the "Unified Power ~~System~~ of Central

Card 1/3

Chronicle

6-58-4-18/18

Siberia and its Importance for the Economic Development of this Region". The following 15 lectures were delivered at the sessions of the department for geodesy: Docent A.I. Agroskin "On the Problem of Angle-Observation in Triangulation" (by which the opinion expressed by Yu.A. Aladzhalov is refuted). Docent V.N. Gan'shin "Efficient Methods of Solving Major Geodetical Problems". Docent A.V. Butkevich "On the Elimination of Successive Approximation in Some Geodetical Calculations". Docent A.A. Vizgin and V.P. Napalkov "The Analysis of the Accuracy of Geodetic Leveling". Chief Engineer I.Ye. Donskikh of the geodetical sector of the Orgenergostroy on "Experience Gathered in Connection with the Determination of Coordinates in the Dam-Tunnel of the Kuybyshev Hydraulic Power Plant". A.A. Meshcheryakov, Candidate of Technical Sciences on "The General Theory of Euler Projection". Chief Geodesist V.P. Utin of the Lengidep Expedition on "Geodetical Work Carried out on the Building Site of the Krasnoyarsk Hydraulic Power Plant". Docent G.I. Znamenshchikov "On the Reducing of the Length of Curved Lines Measured on Maps to the Scale of 1 : 1". (Here it is shown that the method developed by Professor N.M. Volkov has some basic faults). Chief of the Geological Research Expedition of Omsk, Candidate of Technical Sciences D.N. Fialkov on "The Qualitative Characteristic of Vertical Motions of the Earth's

Card 2/3

Chronicle

6-58-4-18/18

Crust in the Steppe Region on the River Irtysh". Docent
V.V.Yegorov "Modern Large-Scale Topographical Maps and Ways and
Means of Attaining their Further Improvement". I.I.Markson
"The Demands made with Respect to the Representation of Soil
Vegetation on Large-Scale Topographical Maps".
Professor K.L. Provorov, director of the NIIGAik, in closing the
conference, gave a summary of the results obtained.

AVAILABLE: Library of Congress

1. Geodetics--Conference
2. Aerial photography--Conference
3. Cartography--Conference

Card 3/3

SHUBIN, N. V., Doc Med Sci -- (diss) "Tick-induced encephalitis in Western Siberia." Tomsk, 1960. 38 pp; (Academy of Medical Sciences USSR); 250 copies; price not given; bibliography at end of text (11 entries); (KL, 24-60, 135)

GOL'DBERG, D.I., prof., otv. red.; ZIVERT, K.N., prof., red.; MASYUKOVA, Ye.M., dots., red.; FETISOV, A.G., prof., red.; SHUBIN, N.V., dots., red.; OSOVSKIY, A.T., tekhn. red.

[Problems in surgery of the esophagus and stomach. Biological effect of rays from the 25 Mev. betatron] Voprosy khirurgii pishchevo-da i zheludka. Biologicheskoe deistvie luchei betatrona 25 MEV. Tomsk, Izd-vo Tomskogo univ., 1960. 354 p. (MIRA 14:8)

1. Tomsk. Tomskiy gosudarstvennyy meditsinskiy institut.
(ALIMENTARY CANAL—SURGERY) (RADIATION—PHYSIOLOGICAL EFFECT)

L 3879-66 EWT(1) GW

AM5023890

BOOK EXPLOITATION

UR/

658.51:528.425/075

445 Teterin, YEGOR Nikolayevich; Shubin, Nikolay Vasil'yevich; Ocheret'ko, Aleksandr Konstsntinovich; Pavlov, Vitaliy Fedorovich 445 48 40 671

Organization and planning of geodetic and topographic operations (Organizatsiya i planirovaniye geodezicheskikh i topograficheskikh rabot) Moscow, Izd-vo "Nedra", 1965. 299 p. illus. Textbook for students in geodetical specialities of higher educational institutions. 4400 copies printed.

TOPIC TAGS: geodesy^{12, 44, 55}, topography, geodetic planning, topographic planning, aerophotography^{20, 44, 55}, economic planning, aerial photographic surveying

PURPOSE AND COVERAGE: This textbook is intended to familiarize practical engineers with problems in economics and labor organization. Economic schooling is of particular importance to students of geodesy and topography, since they will have to solve not only technical but economic problems as well. A special course on the organization and planning of geodetic and topographic work has long

Card 1/4

L 3879-66

AM5023890

3

been in the curriculum at the schools of higher education for geodesists. However, until now no manuals or textbooks on that subject have been available. To fill this need, a group of scientific workers of the Novosibirsk Institute for Engineers of Geodesy, Aerophotography, and Cartography has prepared the present volume, which is intended as a textbook on the subject of the organization and planning of geodetic and topographic work.

TABLE OF CONTENTS [abridged]:

Authors' note -- 3

Introduction -- 5

Ch. I. Administration of geodetic and topographic operations -- 18

Ch. II. Planning of geodetic and topographic work -- 33

Ch. III. Organization of labor and wages. Technical standard-
ization -- 77

Card 2/4

L 3879-66

AM5023890

- Ch. IV. Technical planning of geodetic and topographic operations -- 108
- Ch. V. Organization of basic geodetic work -- 133
- Ch. VI. Organization of topographic-geodetic and topographic work -- 170
- Ch. VII. Some general problems of the organization of field and office work -- 209
- Ch. VIII. Organization of aerial photographic surveying work -- 242
- Ch. IX. Special problems of the organization of topographic-geodetic work in the departments. Cartographic production -- 257
- Ch. X. Financing geodetic and topographic work -- 273
- Ch. XI. Estimating and accounting the geodetic and topographic work -- 279

Card 3/4

L 3879-66

AM5023890

Ch. XII. Production and fiscal analysis of the activity of
enterprises -- 290

SUB CODE: ES

SUBMITTED: 17Apr65 NO REF SOV: 028

OTHER: 003

BVK.
Card 4/4

MARKOV, I.S.; SHUBIN, P.N.

Dairy cattle in the Far North of the Komi A.S.S.R. Trudy Komi fil.,
AN SSSR no.9:3-15 '60. (MIA 15:1)
(KOMI A.S.S.R. DAIRY CATTLE)

IFZHAK, L. I., kand. biolog. nauk (Syktyvkar, Komi filial AN SSSR);
SHUBIN, P. N. (Syktyvkar, Komi filial AN SSSR)

Rare anomaly. Priroda 52 no.1:119 '63. (MIRA 16:1)

(Abnormalities(Animals))
(Inbreeding)

SHUBIN R.P.

Introducing progressive processes and equipment in heat-
treating plants. Metalloved. 1 term. obr. met. no. 6:5-10
Je '63. (MIRA 16:6)

(Steel, Automobile--Heat treatment)
(Case hardening)
(Furnaces, Heat-treating)